

Rohre geschweißt ungeglüht/geglüht DIN 2463 EN ISO 1127 HL 6 m



Norm: DIN 2463 EN ISO 1127
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2
Werkstoff-Nr.: 1.4301 / 1.4541 / 1.4571

Abmessungen		Gewicht KG/M
ø- Aussen	Wandstärke	
6,00	1,00	0,125
8,00	1,00	0,175
10,00	1,00	0,225
	1,50	0,319
12,00	1,00	0,275
	1,50	0,394
	2,00	0,501
14,00	1,00	0,326
	1,50	0,470
	2,00	0,601
15,00	1,00	0,351
	1,20	0,415
	1,50	0,507
	2,00	0,651
16,00	1,00	0,376
	1,50	0,545
	2,00	0,701
17,20	1,60	0,625
	2,00	0,761
	2,30	0,858
18,00	1,00	0,426
	1,50	0,620
	2,00	0,801
20,00	1,00	0,476
	1,50	0,695
	2,00	0,901
	2,50	1,096
	3,00	1,277
21,30	1,50	0,743
	1,60	0,789
	2,00	0,967
	2,50	1,177
	2,60	1,217
22,00	3,00	1,375
	1,00	0,526
	1,50	0,770
	2,00	1,002
	2,00	1,002
23,00	1,50	0,808
24,00	2,00	1,102
25,00	1,00	0,601
	1,50	0,883
	2,00	1,152
	2,50	1,409
	3,00	1,653
26,90	1,50	0,954
	1,60	1,014
	2,00	1,247
	2,50	1,527
	2,60	1,582
3,00	1,795	

Abmessungen		Gewicht KG/M
ø- Aussen	Wandstärke	
28,00	1,00	0,676
33,70	1,50	1,209
	1,60	1,286
	2,00	1,588
	2,50	1,953
	2,60	2,025
	2,90	2,237
	3,00	2,306
34,00	3,20	2,444
	4,00	2,975
	1,00	0,826
35,00	1,50	1,221
	1,50	1,258
36,00	2,00	1,653
	2,50	2,035
	2,00	1,703
38,00	3,00	2,629
	1,00	0,926
	1,50	1,371
	2,00	1,803
	2,50	2,222
40,00	2,60	2,305
	3,00	2,629
	1,00	0,977
	1,50	1,446
	2,00	1,903
42,40	2,50	2,348
	3,00	2,779
	4,00	3,606
	1,50	1,530
	1,60	1,635
43,00	2,00	2,023
	2,50	2,498
	2,60	2,591
	3,00	2,948
	3,20	3,141
44,50	3,60	3,498
	4,00	3,847
	1,50	1,559
45,00	1,50	1,615
	2,00	2,128
	2,60	2,728
48,30	1,50	1,612
	2,00	2,153
	3,00	3,155
	1,50	1,734
48,30	1,60	1,871
	2,00	2,319
	2,50	2,867
	3,00	3,363
	3,20	3,614

Rohre geschweißt ungeglüht/geglüht DIN 2463 EN ISO 1127 HL 6 m



Norm: DIN 2463 EN ISO 1127
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2
Werkstoff-Nr.: 1.4301 / 1.4541 / 1.4571

Abmessungen		Gewicht KG/M	
ø- Aussen	Wandstärke		
52,00	1,00	1,277	
	1,50	1,897	
	2,00	2,504	
53,00	1,50	1,934	
54,00	2,00	2,604	
57,00	1,50	2,085	
	2,00	2,754	
	2,50	3,412	
	3,00	4,056	
60,30	1,50	2,208	
	1,60	2,352	
	2,00	2,920	
	2,30	3,340	
	2,50	3,618	
	2,60	3,757	
	2,90	4,168	
	3,00	4,304	
63,50	1,50	2,208	
	1,60	2,480	
	2,00	3,080	
	2,60	3,819	
	64,00	2,00	3,105
	69,00	2,00	3,355
	70,00	1,50	2,573
		2,00	3,405
2,90		4,873	
3,00		5,033	
73,00	1,50	2,686	
76,10	1,50	2,815	
	1,60	2,985	
	2,00	3,711	
	2,30	4,250	
	2,50	4,612	
	2,60	4,785	
	2,90	5,315	
	3,00	5,494	
	3,20	5,841	
	3,60	6,535	
80,00	1,50	2,948	
	2,00	3,906	
	3,00	5,784	
	4,00	7,613	
	84,00	2,00	4,107
85,00	2,00	4,157	
88,90	1,50	3,282	

Abmessungen		Gewicht KG/M	
ø- Aussen	Wandstärke		
103,00	1,50	3,812	
104,00	2,00	5,108	
108,00	2,00	5,308	
	3,00	7,888	
	4,00	10,417	
114,30	2,00	5,624	
	2,50	6,998	
	2,60	7,272	
	3,00	8,361	
	3,05	8,496	
	3,20	8,902	
129,00	3,60	9,979	
	4,00	11,048	
	129,00	2,00	6,360
	133,00	2,50	8,169
139,70	3,00	9,766	
	4,00	12,921	
	139,70	2,00	6,896
154,00	2,60	8,926	
	3,00	10,269	
	4,00	13,592	
156,00	2,00	7,612	
156,00	3,00	11,490	
159,00	2,00	7,863	
	2,50	9,797	
	3,00	11,720	
168,30	4,00	15,525	
	2,00	8,328	
	2,60	10,788	
	3,00	12,417	
204,00	4,00	16,456	
	204,00	2,00	10,116
	206,00	3,00	15,240
	219,10	2,00	10,872
254,00	2,60	14,100	
	3,00	16,233	
	4,00	21,544	
	5,00	26,805	
	254,00	2,00	12,620
273,00	3,00	19,000	
	2,60	17,600	
	3,00	20,287	
306,00	4,00	26,940	
	3,00	22,761	
	323,90	3,00	24,106
355,60	4,00	32,041	
	5,00	39,926	
355,60	3,00	26,490	
355,60	4,00	35,216	

