

Rohr nahtlos DIN 2462 EN ISO 1127 HL 6 m



Norm: DIN 2462 EN ISO 1127
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2
Werkstoff-Nr.: 1.4301 / 1.4541 / 1.4571

Abmessungen		Gewicht KG/M	
ø- Aussen	Wandstärke		
4,00	0,50	0,044	
	1,00	0,075	
5,00	0,50	0,055	
	1,00	1,000	
6,00	0,50	0,069	
	1,00	0,125	
	1,50	0,169	
	2,00	0,200	
7,00	1,00	0,069	
8,00	0,50	0,100	
	1,00	0,175	
	1,50	0,175	
	2,00	0,300	
10,00	0,50	0,125	
	1,00	0,225	
	1,50	0,319	
	1,60	0,345	
	2,00	0,401	
10,20	2,50	0,470	
	3,00	0,526	
	10,20	2,00	0,333
	11,00	1,50	0,357
12,00	0,50	0,144	
	1,00	0,276	
	1,50	0,394	
	2,00	0,501	
	2,50	0,595	
	2,90	0,661	
	3,00	0,676	
4,00	0,801		
13,00	1,50	0,477	
13,50	1,60	0,477	
	2,00	0,576	
	2,30	0,645	
	2,50	0,710	
	2,90	0,770	
14,00	1,00	0,326	
	1,50	0,470	
	2,00	0,601	
	2,00	0,601	
	2,50	0,720	
	3,00	0,826	
15,00	1,00	0,351	
	1,50	0,509	
	2,00	0,651	
	2,50	0,783	
15,00	3,00	0,850	
	4,00	1,105	

Abmessungen		Gewicht KG/M
ø- Aussen	Wandstärke	
16,00	1,00	0,376
	1,50	0,545
16,00	1,60	0,545
	2,00	0,701
	2,50	0,845
	3,00	0,976
16,00	4,00	1,202
	17,00	1,50
17,00	3,00	1,052
	17,20	1,60
17,20	1,80	0,696
	2,00	0,761
	2,30	0,860
	2,90	1,038
	3,20	1,122
18,00	1,00	0,426
	1,50	0,620
	2,00	0,801
	2,50	0,970
	3,00	1,127
18,00	3,50	1,271
	4,00	1,402
	20,00	1,00
20,00	1,50	0,695
	2,00	0,901
	2,50	1,096
	3,00	1,277
	3,50	1,446
	4,00	1,802
	5,00	1,878
21,00	3,00	1,352
21,30	1,60	0,789
	2,00	0,967
	2,60	1,217
	2,90	1,336
	3,20	1,450
22,00	1,00	0,526
	1,50	0,770
	2,00	1,002
	2,50	1,260
	3,00	1,432
	4,00	1,803
24,00	1,50	0,845
	2,00	1,102
	4,00	2,003
25,00	1,00	0,605
	1,50	0,890
	2,00	1,152

Rohr nahtlos DIN 2462 EN ISO 1127 HL 6 m



Norm: DIN 2462 EN ISO 1127
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2
Werkstoff-Nr.: 1.4301 / 1.4541 / 1.4571

Abmessungen		Gewicht KG/M
ø- Aussen	Wandstärke	
25,00	2,50	1,409
	3,00	1,653
	3,50	1,884
	4,00	2,103
	5,00	2,504
26,90	6,00	2,850
	1,60	1,043
	2,00	1,247
	2,30	1,417
	2,60	1,582
27,00	2,90	1,750
	3,20	1,899
	4,00	2,240
	3,00	1,803
	4,00	2,304
28,00	1,00	0,676
	1,50	0,995
	2,00	1,302
	2,50	1,596
	3,00	1,878
	3,50	2,147
	4,00	2,404
30,00	5,00	2,880
	1,00	0,726
	1,50	1,070
	1,60	1,140
	2,00	1,402
	2,60	1,784
32,00	3,00	2,028
	3,50	2,322
	4,00	2,604
	5,00	3,130
	1,00	0,776
	1,50	1,146
33,00	2,00	1,502
	2,50	1,847
	3,00	2,178
	4,00	2,804
	1,50	1,183
33,70	1,60	1,324
	2,00	1,588
	2,60	2,025
	2,90	2,237
	3,20	2,444
	3,60	2,713
	4,00	3,007
34,00	5,00	3,590
	2,00	1,603

Abmessungen		Gewicht KG/M	
ø- Aussen	Wandstärke		
34,00	3,50	2,673	
	4,00	3,020	
	5,00	3,631	
	5,50	3,940	
35,00	1,50	1,258	
	2,00	1,653	
	2,50	2,035	
	3,00	2,404	
	4,00	3,105	
36,00	5,00	3,756	
	2,00	1,703	
	38,00	1,50	1,371
	2,00	1,810	
	2,60	2,320	
40,00	3,00	2,629	
	3,60	3,101	
	4,00	3,405	
	5,00	4,132	
	6,00	5,000	
42,00	6,30	6,610	
	1,00	0,977	
	1,50	1,446	
	2,00	1,903	
	2,50	2,348	
	3,00	2,779	
42,40	4,00	3,606	
	5,00	4,382	
	3,00	2,930	
	6,00	5,409	
43,00	2,00	2,023	
	2,60	2,591	
	3,20	3,141	
	3,60	3,441	
	4,10	3,889	
	4,50	4,270	
44,00	5,00	5,165	
	6,00	5,409	
	1,50	1,559	
	2,00	2,103	
	44,50	2,00	2,128
45,00	2,60	2,728	
	2,90	3,021	
	4,00	4,056	
	5,50	5,371	
	1,60	1,739	
45,00	2,00	2,128	
	3,00	3,155	
	5,00	5,008	

Rohr nahtlos DIN 2462 EN ISO 1127 HL 6 m



Norm: DIN 2462 EN ISO 1127
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2
Werkstoff-Nr.: 1.4301 / 1.4541 / 1.4571

Abmessungen		Gewicht KG/M
ø- Aussen	Wandstärke	
48,30	2,00	2,319
	2,60	2,975
	3,00	3,614
	3,20	3,614
	3,60	4,108
	4,00	4,487
	5,00	5,421
50,00	8,00	8,070
	1,50	1,822
	2,00	2,404
	2,50	2,974
	3,00	3,531
	4,00	4,620
51,00	5,00	5,634
	6,00	6,611
	2,00	2,454
	2,60	3,151
52,00	4,00	4,708
	7,00	7,750
	2,00	2,504
53,00	4,00	4,808
	1,50	1,934
54,00	3,00	3,756
	2,00	2,604
55,00	2,50	3,290
	5,00	6,260
57,00	2,00	2,754
	2,90	3,929
	3,50	4,689
	4,00	5,308
	5,00	6,510
	6,50	8,219
60,00	5,00	6,886
	6,30	8,676
60,30	1,60	2,352
	2,00	3,757
	2,60	3,910
	2,90	4,168
	3,20	4,800
	3,60	5,111
	4,00	5,650
	4,50	6,288
	5,00	6,920
	7,10	9,458
63,50	8,00	10,477
	10,00	12,640
	1,60	2,480
	2,50	3,819

Abmessungen		Gewicht KG/M	
ø- Aussen	Wandstärke		
63,50	2,60	3,819	
	3,50	5,280	
	5,00	7,324	
64,00	2,00	3,105	
	65,00	2,50	3,913
68,00	3,50	5,390	
	4,00	6,410	
70,00	2,00	3,405	
	2,50	4,240	
	2,90	4,888	
	4,00	6,611	
	5,00	8,138	
	6,30	10,048	
75,00	7,00	11,080	
	2,50	4,539	
	5,00	8,790	
	76,00	5,00	8,889
76,10	6,00	10,510	
	2,00	3,711	
	2,30	4,250	
80,00	2,60	4,785	
	2,90	5,932	
	3,20	5,860	
	3,60	6,535	
	4,00	7,222	
	4,50	8,068	
	5,00	8,889	
	6,30	11,011	
82,50	7,10	12,267	
	10,00	17,000	
	12,50	19,970	
	2,00	3,906	
	2,50	4,852	
	4,00	7,612	
	5,00	9,390	
	3,60	7,022	
	88,90	2,00	4,352
		2,60	5,618
2,90		6,970	
3,10		6,557	
3,20		6,897	
3,60		7,689	
4,00		8,530	
4,10		8,605	
4,50		9,510	
5,00		10,451	
	6,30	13,030	
	10,00	19,757	

Rohr nahtlos DIN 2462 EN ISO 1127 HL 6 m



Norm: DIN 2462 EN ISO 1127
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2
Werkstoff-Nr.: 1.4301 / 1.4541 / 1.4571

Abmessungen		Gewicht KG/M
ø- Aussen	Wandstärke	
97,00	4,00	9,315
100,00	3,00	7,287
	5,00	11,894
101,60	3,60	8,834
	4,10	9,893
102,00	6,50	15,590
108,00	3,00	7,888
	3,60	9,411
	4,00	10,417
	5,00	12,896
	6,30	16,043
114,30	2,00	5,624
	2,60	7,272
	3,20	8,902
	3,60	9,979
	4,00	11,048
	4,50	12,372
	5,40	14,725
	6,30	17,037
121,00	7,10	19,058
	14,20	35,592
	4,00	11,719

Abmessungen		Gewicht KG/M
ø- Aussen	Wandstärke	
127,00	4,00	12,320
	5,00	15,274
133,00	4,00	12,921
	5,00	16,026
	6,30	19,987
139,70	4,00	21,040
	5,00	16,864
	6,30	21,044
	7,10	23,574
159,00	4,50	17,409
	6,30	24,089
	8,00	30,260
168,30	4,00	16,460
	4,50	18,457
	5,00	20,500
	6,30	26,485
219,10	4,00	20,274
	6,30	33,570
	10,00	52,359
323,90	9,50	74,942
	20,00	157,060
	21,40	162,040

Andere Abmessungen oder Werkstoffe auf Anfrage.

Industriestraße 3 76470 Ötigheim Tel. 0 72 22 / 92 88 -12/18 Fax 0 72 22 / 92 88 -80
 e-mail: info@edelstahlhandel-oetigheim.de