

Rohrbogen geschweißt DIN 2605 Norm 3S/D+100



Norm: DIN 2605 90° Norm 3S (r=1,5d)/D+100 (r=d+100)
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B
Werkstoff-Nr.: 1.4541 / 1.4571

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
12,00	1,00	0,020
	1,50	0,020
	2,00	0,030
13,50	1,60	0,020
	2,00	0,030
	2,30	0,040
14,00	1,50	0,020
	2,00	0,030
15,00	1,50	0,020
	2,00	0,030
16,00	1,50	0,020
	2,00	0,030
17,20	1,60	0,020
	2,00	0,030
	2,30	0,040
18,00	1,50	0,020
	2,00	0,030
20,00	1,50	0,030
	2,00	0,030
	2,50	0,040
21,30	1,60	0,030
	2,00	0,040
	2,60	0,060
21,34	2,11	0,070
	2,77	0,080
23,00	1,50	0,040
25,00	1,50	0,040
	2,00	0,050
	2,50	0,060
26,67	2,11	0,070
	2,87	0,080
26,90	1,60	0,050
	2,00	0,060
	2,60	0,080
28,00	1,50	0,060
	2,00	0,070
30,00	1,50	0,050
	2,00	0,070
	2,50	0,090
33,40	2,77	0,120
	3,38	0,150
33,70	1,60	0,080
	2,00	0,100
	2,60	0,120
	2,90	0,130
	3,20	0,140

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
35,00	1,50	0,100
	2,00	0,120
36,00	2,00	0,130
38,00	1,50	0,110
	2,00	0,130
	2,50	0,160
40,00	2,00	0,160
42,16	2,77	0,200
	3,56	0,260
42,40	1,60	0,140
	2,00	0,160
	2,60	0,190
	3,20	0,230
43,00	1,50	0,140
44,50	1,50	0,150
	2,00	0,170
	2,50	0,220
	2,60	0,220
48,26	2,77	0,270
	3,68	0,360
48,30	1,60	0,190
	2,00	0,220
	2,60	0,260
	3,20	0,320
51,00	1,60	0,210
	2,00	0,310
53,00	1,50	0,260
54,00	2,00	0,340
57,00	1,50	0,280
	2,00	0,340
	2,50	0,390
	3,00	0,480
60,30	1,60	0,290
	2,00	0,340
	2,60	0,440
	2,77	0,460
	2,90	0,900
	3,20	0,540
	3,60	0,620
63,50	1,50	0,310
	1,60	0,310
68,00	1,50	0,380
69,00	2,00	0,500
70,00	2,00	0,500
	3,00	0,720
76,10	1,60	0,500

Rohrbogen geschweißt DIN 2605 Norm 3S/D+100



Norm: DIN 2605 90° Norm 3S (r=1,5d)/D+100 (r=d+100)
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B
Werkstoff-Nr.: 1.4541 / 1.4571

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
76,10	2,00	0,620
	2,30	0,720
	2,60	0,770
	2,90	0,880
	3,00	0,900
	3,20	0,970
	3,60	1,080
	4,00	1,180
83,00	1,50	0,590
84,00	2,00	0,750
85,00	2,00	0,750
88,90	2,00	0,810
	2,30	0,940
	2,60	1,020
	2,90	1,150
	3,20	1,220
	3,60	1,380
	4,00	1,760
101,60	2,00	1,050
	2,50	1,310
	2,60	1,310
	3,00	1,560
	3,60	1,870
	4,00	2,080
103,00	1,50	0,950
104,00	2,00	1,100
108,00	2,00	1,200
	2,50	1,300
	2,90	1,790
	3,00	1,850
	3,20	1,970
	4,00	2,200
	5,00	2,750
114,30	2,00	1,300
	2,60	1,600
	2,90	1,790
	3,05	2,090
	3,20	2,120
	3,60	2,350
	4,00	2,700
	4,50	3,600
144,30	5,00	3,710
	5,40	3,710
129,00	2,00	1,900
133,00	2,60	2,340
	3,00	2,850

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
133,00	3,20	3,150
	4,00	3,620
	5,00	4,650
139,70	2,00	1,970
	2,60	2,560
	2,90	2,980
	3,20	3,400
	4,00	4,090
	5,00	5,110
154,00	2,00	2,750
159,00	2,00	2,580
	2,60	3,350
	3,00	3,900
	3,20	4,160
	4,00	5,150
	5,00	6,440
	6,00	7,800
168,30	2,00	2,890
	2,60	3,750
	2,90	4,320
	3,20	4,770
	3,60	5,190
	4,00	5,900
	5,00	7,200
	7,11	10,250
204,00	2,00	5,050
205,00	2,50	6,000
206,00	3,00	7,210
219,10	2,60	6,500
	2,90	7,550
	3,00	7,800
	3,20	8,320
	3,60	9,100
	4,00	10,380
	5,00	13,200
	6,00	16,400
254,00	2,00	6,970
255,00	2,50	8,750
256,00	3,00	10,500
273,00	2,60	10,200
	2,90	11,800
	3,00	12,200
	3,20	13,000
	4,00	16,300
	5,00	20,400
	6,00	20,400

Rohrbogen geschweißt DIN 2605 Norm 3S/D+100



Norm: DIN 2605 90° Norm 3S (r=1,5d)/D+100 (r=d+100)
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B
Werkstoff-Nr.: 1.4541 / 1.4571

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
306,00	3,00	14,400
323,90	2,60	15,100
	2,90	16,800
	3,00	17,400
	4,00	23,200
	5,00	29,400
355,60	6,00	34,800
	2,90	21,600
	3,00	22,300
	3,20	23,700
	4,00	29,700

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
355,60	5,00	37,400
	6,00	46,800
356,00	3,00	22,300
	4,00	27,600
406,00	2,90	25,900
	3,00	26,800
	3,20	28,600
	4,00	38,100
	5,00	49,300
	6,00	57,200
	8,00	75,000

Andere Abmessungen oder Werkstoffe auf Anfrage.

Industriestraße 3 76470 Ötigheim Tel. 0 72 22 / 92 88 -12/18 Fax 0 72 22 / 92 88 -80
e-mail: info@edelstahlhandel-oetigheim.de