

Rohrbogen nahtlos DIN 2605 Norm 3S



Norm: DIN 2605 90° Norm 3S (r=1,5d)
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und teilweise AD-W2
Werkstoff-Nr.: 1.4541 / 1.4571

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
12,00	1,00	0,020
	1,50	0,020
	2,00	0,030
13,50	1,60	0,020
	2,00	0,030
	2,30	0,040
14,00	1,50	0,020
	2,00	0,030
15,00	1,50	0,020
	2,00	0,030
16,00	1,50	0,020
	2,00	0,030
17,20	2,00	0,030
	2,30	0,040
18,00	1,50	0,020
	2,00	0,030
20,00	1,50	0,030
	2,00	0,030
	2,50	0,040
21,30	1,60	0,030
	2,00	0,040
	2,60	0,060
	3,20	0,080
21,34	3,73	0,090
	2,11	0,070
	2,77	0,080
25,00	3,73	0,090
	2,00	0,050
	2,50	0,060
26,67	3,00	0,070
	4,00	0,100
	5,00	0,120
	2,11	0,070
	2,87	0,080
26,90	3,91	0,100
	1,60	0,050
	2,00	0,060
28,00	2,30	0,070
	2,60	0,080
	3,20	0,100
	3,91	0,130
	4,00	0,130
28,00	1,50	0,060
	2,00	0,070
	2,50	0,090

Abmessungen		Gewicht KG/St.	
ø- Aussen	Wandstärke		
30,00	2,00	0,070	
	2,50	0,090	
	3,00	0,110	
31,80	4,00	0,150	
	5,00	0,180	
	2,00	0,080	
33,40	2,60	0,100	
	3,50	0,140	
	2,77	0,120	
33,70	3,38	0,150	
	4,55	0,190	
	2,00	0,100	
35,00	2,60	0,120	
	2,90	0,130	
	3,20	0,140	
	3,38	0,160	
	3,60	0,180	
36,00	3,68	0,180	
	4,00	0,190	
	4,55	0,210	
	5,00	0,230	
38,00	2,00	0,120	
	2,50	0,160	
40,00	2,00	0,130	
	38,00	2,00	0,130
	2,50	0,160	
	2,60	0,170	
	3,00	0,200	
42,16	4,00	0,260	
	5,00	0,320	
	6,00	0,340	
	2,00	0,160	
42,40	3,00	0,240	
	5,00	0,380	
	2,77	0,200	
42,40	3,56	0,260	
	4,85	0,340	
	2,00	0,160	
	2,60	0,190	
	3,00	0,230	
42,40	3,20	0,230	
	3,60	0,260	
	4,00	0,320	
	5,00	0,390	
	6,30	0,450	

Rohrbogen nahtlos DIN 2605 Norm 3S



Norm: DIN 2605 90° Norm 3S (r=1,5d)
Abnahmen/Zeugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und teilweise AD-W2
Werkstoff-Nr.: 1.4541 / 1.4571

Abmessungen		Gewicht KG/St.	
ø- Aussen	Wandstärke		
44,50	2,00	0,170	
	2,50	0,220	
	2,60	0,300	
	2,90	0,270	
	3,20	0,300	
	4,00	0,340	
48,26	5,00	0,440	
	2,77	0,270	
	3,68	0,360	
48,30	5,08	0,490	
	2,00	0,220	
	2,60	0,260	
	2,90	0,300	
	3,20	0,320	
	3,68	0,370	
	4,00	0,420	
51,00	4,05	0,430	
	5,00	0,520	
	2,00	0,310	
	2,50	0,350	
	2,60	0,350	
	2,90	0,420	
54,00	4,00	0,620	
	2,00	0,340	
	57,00	2,00	0,334
	2,50	0,390	
60,30	2,60	0,390	
	2,90	0,480	
	4,00	0,640	
	5,00	0,800	
	6,30	0,960	
	2,00	0,340	
	2,60	0,440	
	2,77	0,460	
63,50	2,90	0,490	
	3,20	0,540	
	3,60	0,620	
	3,91	0,620	
	4,00	0,680	
	4,50	0,780	
	5,00	0,820	
	5,45	0,890	
	5,54	0,900	
	5,60	0,950	
	8,00	1,340	
	8,80	1,450	
	10,00	1,640	

Abmessungen		Gewicht KG/St.	
ø- Aussen	Wandstärke		
63,50	2,60	0,510	
	3,00	0,580	
70,00	2,00	0,500	
	2,90	0,720	
	3,00	0,720	
	4,00	1,000	
	5,00	1,200	
73,03	73,03	3,05	1,000
	5,16	1,390	
	7,01	1,700	
76,10	76,10	2,00	0,620
	2,60	0,770	
	2,90	0,880	
	3,20	0,970	
	3,60	1,080	
	4,00	1,180	
	4,50	1,320	
	5,00	1,470	
	6,00	1,760	
	10,00	2,940	
82,50	82,50	3,20	1,210
	3,60	1,360	
88,90	88,90	2,00	0,810
	2,60	1,020	
	2,90	1,150	
	3,05	1,200	
	3,20	1,220	
	3,60	1,380	
	4,05	1,760	
	5,00	1,870	
	5,40	2,060	
	5,49	2,060	
	5,60	2,060	
	6,00	2,420	
	6,30	2,540	
7,62	3,030		
10,00	3,740		
11,00	3,940		
101,60	101,60	3,05	1,660
	3,20	1,660	
	3,60	1,870	
	4,00	2,080	
	5,74	2,850	
108,00	108,00	2,90	1,850
	3,00	1,850	
	3,20	1,970	
	3,60	2,070	

Rohrbogen nahtlos DIN 2605 Norm 3S



Norm: DIN 2605 90° Norm 3S (r=1,5d)
Abnahmen/Zugnisse: DIN 50049/3.1B bzw. EN 10204/3.1B und teilweise AD-W2
Werkstoff-Nr.: 1.4541 / 1.4571

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
108,00	4,00	2,200
	5	2,750
	6,30	3,800
	9,00	4,950
114,30	2,60	1,600
	2,90	2,000
	3,05	2,090
	3,20	2,120
	3,60	2,350
	4,00	2,700
	4,50	3,000
	5,40	3,710
	6,02	4,140
	8,56	5,900
133,00	4,00	3,620
	6,30	3,620
139,70	4,00	4,090
	5,00	5,500
	7,10	7,100
141,30	3,40	3,500
	6,55	6,600
159,00	4,50	5,820

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
159,00	6,30	9,000
168,30	3,40	4,950
	4,50	6,520
	5,00	7,200
	5,60	7,950
	7,11	10,250
	10,92	15,400
219,10	3,76	9,700
	5,90	16,000
	6,30	16,400
	8,18	22,400
	12,70	30,500
	18,25	43,000
273,00	9,27	35,000
	12,70	49,000
	20,00	75,000
323,90	9,52	56,000
	12,70	108,000
406,40	12,50	116,000
	17,50	161,000
	18,00	168,000
	30,90	270,000

Andere Abmessungen oder Werkstoffe auf Anfrage.

Industriestraße 3 76470 Ötigheim Tel. 0 72 22 / 92 88 -12/18 Fax 0 72 22 / 92 88 -80
 e-mail: info@edelstahlhandel-oetigheim.de