

## Rundstahl gewalzt EN 10060 HL 4-6 m



**Norm:** EN 10060 ehemals DIN 1013  
**Abnahmen/Zeugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2  
**Werkstoff-Nr.:** 1.4301 / 1.4305 / 1.4541 / 1.4571 + Sonderwerkstoffe

| Abmessung<br>Ø | Gewicht<br>KG/M |
|----------------|-----------------|
| 20             | 2,470           |
| 21             | 2,720           |
| 22             | 2,980           |
| 23             | 3,260           |
| 24             | 3,550           |
| 25             | 3,850           |
| 26             | 4,170           |
| 27             | 4,500           |
| 28             | 4,830           |
| 30             | 5,550           |
| 32             | 6,310           |
| 33             | 6,740           |
| 34             | 7,130           |
| 35             | 7,553           |
| 36             | 7,990           |
| 38             | 8,900           |
| 40             | 9,870           |
| 42             | 10,880          |
| 44             | 11,940          |
| 45             | 12,490          |
| 48             | 14,210          |
| 50             | 15,410          |

| Abmessung<br>Ø | Gewicht<br>KG/M |
|----------------|-----------------|
| 52             | 16,670          |
| 55             | 18,650          |
| 60             | 22,200          |
| 62             | 23,700          |
| 65             | 26,050          |
| 70             | 30,210          |
| 75             | 34,680          |
| 80             | 39,460          |
| 85             | 44,500          |
| 90             | 49,940          |
| 95             | 55,640          |
| 100            | 61,550          |
| 105            | 67,970          |
| 110            | 74,600          |
| 115            | 81,540          |
| 120            | 88,780          |
| 125            | 96,330          |
| 130            | 104,200         |
| 135            | 112,360         |
| 140            | 120,840         |
| 145            | 129,630         |
| 150            | 138,720         |

| Abmessung<br>Ø | Gewicht<br>KG/M |
|----------------|-----------------|
| 160            | 157,830         |
| 170            | 178,180         |
| 180            | 199,760         |
| 190            | 222,570         |
| 200            | 246,620         |
| 210            | 271,900         |
| 220            | 298,400         |
| 230            | 326,100         |
| 240            | 355,100         |
| 250            | 385,300         |
| 260            | 416,800         |
| 270            | 449,500         |
| 280            | 483,400         |
| 290            | 518,300         |
| 300            | 558,000         |
| 310            | 592,500         |
| 325            | 651,000         |
| 340            | 712,000         |
| 350            | 755,300         |

## Rundstahl blank gezogen h9 EN 10278 HL ca. 3 m



**Norm:** EN 10278 ehemals DIN 671  
**Abnahmen/Zeugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2  
**Werkstoff-Nr.:** 1.4301 / 1.4305 / 1.4541 / 1.4571 + Sonderwerkstoffe

| Abmessung<br>Ø | Gewicht<br>KG/M |
|----------------|-----------------|
| 4              | 0,099           |
| 5              | 0,154           |
| 6              | 0,222           |
| 7              | 0,302           |
| 8              | 0,395           |
| 9              | 0,499           |
| 10             | 0,617           |
| 12             | 0,888           |
| 13             | 1,042           |
| 14             | 1,208           |
| 15             | 1,387           |
| 16             | 1,578           |
| 17             | 1,782           |
| 18             | 1,998           |
| 19             | 2,226           |

| Abmessung<br>Ø | Gewicht<br>KG/M |
|----------------|-----------------|
| 20             | 2,466           |
| 21             | 2,714           |
| 22             | 2,984           |
| 23             | 3,261           |
| 25             | 3,853           |
| 26             | 4,168           |
| 27             | 4,495           |
| 28             | 4,834           |
| 30             | 5,549           |
| 33             | 6,714           |
| 34             | 7,130           |
| 35             | 7,550           |
| 36             | 7,990           |
| 40             | 9,870           |
| 42             | 10,880          |

| Abmessung<br>Ø | Gewicht<br>KG/M |
|----------------|-----------------|
| 45             | 12,480          |
| 48             | 14,200          |
| 50             | 15,410          |
| 52             | 16,760          |
| 55             | 18,650          |
| 58             | 20,680          |
| 60             | 22,200          |
| 65             | 26,050          |
| 70             | 30,210          |
| 75             | 34,680          |
| 80             | 39,460          |
| 85             | 44,500          |
| 90             | 49,940          |
| 95             | 55,640          |
| 100            | 61,650          |

# Rundstahl

## Rundstahl geschliffen Korn 240 HL 6 m



**Norm:** Keine  
**Abnahmen/Zugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2  
**Werkstoff-Nr.:** 1.4301

| Abmessung<br>Ø | Gewicht<br>KG/M |
|----------------|-----------------|
| 8              | 0,395           |
| 10             | 0,617           |
| 12             | 0,888           |
| 14             | 1,208           |
| 15             | 1,387           |
| 16             | 1,578           |
| 18             | 1,998           |
| 20             | 2,466           |

Andere Abmessungen oder Werkstoffe auf Anfrage.

Industriestraße 3 76470 Ötigheim Tel. 0 72 22 / 92 88 -12/18 Fax 0 72 22 / 92 88 -80  
e-mail: [info@edelstahlhandel-oetigheim.de](mailto:info@edelstahlhandel-oetigheim.de)