

## T-Stücke geschweißt (gepresst/gezogen/ingeschweißt)



**Norm:** EN 10253-4 / DIN 2615 (gepresst/gezogen)  
**Abnahmen/Zugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B  
 DIN 50049/3.1B Vormaterial  
**Werkstoff-Nr.:** 1.4301 / 1.4541 / 1.4571 / 1.4404 + Sonderwerkstoffe

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
17,20	1,60	0,040
21,30	2,00	0,090
	2,60	0,110
	2,00	0,110
25,00	2,00	0,110
26,90	2,00	0,120
30,00	2,00	0,170
33,70	2,00	0,190
	3,00	0,280
	2,00	0,320
42,40	2,60	0,410
	3,00	0,480
	2,00	0,420
44,50	2,00	0,460
	2,60	0,590
	3,00	0,690
48,30	2,00	0,540
	2,60	0,740
	3,00	0,860
54,00	2,00	0,570
	2,60	0,740
	3,00	0,860
60,30	2,00	0,730
	2,60	0,800
	3,00	1,040
70,00	2,60	1,040
	3,00	1,290
	3,00	1,290
76,10	3,00	1,290
	3,20	1,850
	2,00	1,570
84,00	2,00	1,730
	2,60	2,250
	3,00	2,670
	4,00	3,560
88,90	2,00	1,120
	2,60	1,450
	3,00	1,290
104,00	3,00	1,700
	3,20	1,850
	2,00	1,570
114,30	2,00	1,730
	2,60	2,250
	3,00	2,670
	4,00	3,560

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
129,00	2,00	1,950
139,70	2,00	2,110
	2,60	2,740
	3,00	4,400
154,00	4,00	4,800
	2,00	2,330
	2,60	3,300
168,30	3,00	6,000
	4,00	6,440
	2,00	3,080
204,00	2,00	3,310
	3,00	7,810
	4,00	12,700
219,10	5,00	16,420
	2,00	4,130
	3,00	11,000
273,00	4,00	14,660
	5,00	18,330
	3,00	15,300
323,90	4,00	20,400
	5,00	25,500
	3,00	16,790
355,60	4,00	22,390
	5,00	27,980
	3,00	19,190
406,40	4,00	25,580
	5,00	31,980
	6,00	38,370
457,00	3,00	21,570
	4,00	28,760
	5,00	35,950
508,00	6,00	43,140
	3,00	23,970
	4,00	31,960
580,00	5,00	39,960
	6,00	47,950

## Reduzierte T-Stücke nahtlos/geschweißt



**Norm:** EN 10253-4 / DIN 2615 (nahtlos/geschweißt)  
**Abnahmen/Zugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und Teilweise AD-W2  
 DIN 50049/3.1B Vormaterial  
**Werkstoff-Nr.:** 1.4301 / 1.4541 / 1.4571 / 1.4404 + Sonderwerkstoffe

Abmessungen		Gewicht KG/St.	
ø- Aussen	Wandstärke		
26,9/21,3	2,3/2,0	0,150	
	2,9/2,6	0,180	
	4,0/3,6	0,220	
33,7/21,3	2,0/2,0	0,220	
	2,9/2,3	0,280	
	3,6/2,9	0,350	
	4,5/4,0	0,400	
33,7/26,9	2,0/2,0	0,220	
	2,9/2,3	0,280	
	3,0/3,0	0,320	
	3,6/2,9	0,350	
42,4/21,3	2,0/2,0	0,320	
	2,6/2,0	0,360	
	2,6/2,3	0,340	
42,4/26,9	2,0/2,0	0,300	
	2,6/2,3	0,380	
	3,0/3,0	0,460	
	3,6/2,9	0,520	
42,4/33,7	2,0/2,0	0,320	
	2,6/2,3	0,380	
	2,6/2,6	0,420	
	3,0/3,0	0,460	
	3,6/2,9	0,550	
48,3/21,3	2,0/2,0	0,350	
48,3/26,9	2,0/2,0	0,440	
	2,6/2,3	0,540	
	3,0/3,0	0,660	
	3,6/2,9	0,730	
48,3/33,7	2,0/2,0	0,540	
	2,6/2,0	0,610	
	2,6/2,3	0,650	
	3,0/3,0	0,800	
	3,6/2,9	0,730	
	5,1/4,5	1,050	
48,3/42,4	2,0/2,0	0,660	
	2,6/2,3	0,800	
	3,0/3,0	0,980	
60,3/21,3	2,9/2,6	0,720	
	60,3/26,9	2,0/2,0	0,540
		2,6/2,3	0,640
		2,9/2,6	0,720
60,3/33,7	3,0/3,0	0,780	
	2,0/2,0	0,640	
	2,6/2,3	0,780	
2,9/2,6	0,900		

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
60,3/33,7	3,0/3,0	1,100
	4,0/3,6	1,090
	5,6/4,5	1,400
60,3/42,4	2,0/2,0	0,550
	2,6/2,3	0,670
	2,9/2,6	0,760
	3,0/3,0	0,830
	4,0/3,6	1,100
60,3/48,3	2,0/2,0	0,570
	2,6/2,3	0,700
	2,9/2,6	0,790
	3,0/3,0	0,860
	4,0/3,6	1,100
76,1/33,7	5,6/5,1	1,400
	2,0/2,0	0,640
	3,0/3,0	0,960
76,1/42,4	2,0/2,0	0,810
	2,6/2,3	0,990
	2,9/2,6	1,120
	3,0/3,0	1,210
	5,6/3,6	2,100
76,1/48,3	2,0/2,0	0,840
	2,6/2,3	1,020
	2,9/2,6	1,160
	3,0/3,0	1,260
	5,6/3,6	2,100
76,1/60,3	2,0/2,0	1,140
	2,6/2,3	1,390
	2,9/2,3	1,200
	3,0/3,0	1,710
	4,0/4,0	2,280
88,9/42,4	5,6/4,0	2,200
	2,0/2,0	1,030
	3,0/3,0	1,540
88,9/48,3	2,0/2,0	1,170
	2,9/2,6	1,600
	3,0/3,0	1,750
	3,2/2,6	1,700
	5,6/3,6	2,800
88,9/60,3	2,0/2,0	1,460
	2,9/2,6	1,660
	3,0/3,0	2,180
	4,0/4,0	2,420
	3,2/2,9	1,850
	5,6/4,0	2,900
7,6/6,3	4,000	

# T-Stücke

## Reduzierte T-Stücke nahtlos/geschweißt



**Norm:** EN 10253-4 / DIN 2615 (nahtlos/geschweißt)  
**Abnahmen/Zeugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und Teilweise AD-W2  
 DIN 50049/3.1B Vormaterial  
**Werkstoff-Nr.:** 1.4301 / 1.4541 / 1.4571 / 1.4404 + Sonderwerkstoffe

Abmessungen		Gewicht KG/St.	
ø- Aussen	Wandstärke		
88,9/76,1	2,0/2,0	1,480	
	2,9/2,6	1,700	
	3,0/3,0	2,280	
	4,0/4,0	2,520	
	3,2/2,9	1,850	
114,3/48,3	2,0/2,0	0,960	
	3,0/3,0	2,280	
	4,0/4,0	2,520	
	3,2/2,9	1,850	
114,3/48,3	2,0/2,0	0,960	
	3,0/3,0	1,440	
114,3/60,3	2,0/2,0	1,800	
	3,0/2,6	2,520	
	3,0/3,0	2,700	
	3,6/2,9	2,900	
	4,0/4,0	3,600	
	6,3/4,0	4,850	
	8,8/5,6	6,600	
114,3/76,1	2,0/2,0	2,270	
	3,0/2,6	3,180	
	3,0/3,0	3,400	
	3,6/2,9	3,000	
	4,0/4,0	4,540	
114,3/88,9	2,0/2,0	2,650	
	3,0/2,6	3,710	
	3,0/3,0	3,970	
	3,6/3,2	3,000	
	4,0/4,0	5,300	
139,7/60,3	2,0/2,0	2,190	
	3,0/3,0	3,280	
	4,0/4,0	4,380	
	139,7/76,1	2,0/2,0	2,760
		3,0/2,6	3,860
3,0/3,0		4,150	
4,0/2,9		4,500	
139,7/76,1	4,0/4,0	5,520	
	139,7/88,9	3,0/2,6	4,840
		3,0/3,0	6,450
		4,0/3,2	8,060
4,0/4,0		4,510	
5,0/5,0	5,790		
139,7/114,3	3,0/3,0	6,220	
	3,2/2,6	8,290	
	4,0/3,6	10,360	
	4,0/4,0	5,800	
	5,0/5,0	7,870	

Abmessungen		Gewicht KG/St.	
ø- Aussen	Wandstärke		
168,3/60,3	3,0/3,0	3,950	
	4,0/4,0	5,260	
168,3/76,1	2,0/2,0	3,320	
	3,0/3,0	4,980	
	4,0/4,0	6,640	
168,3/88,9	3,0/2,6	3,790	
	3,0/3,0	5,050	
	4,0/4,0	3,530	
	4,5/3,2	4,850	
168,3/88,9	7,1/5,6	7,990	
	168,3/114,3	3,0/2,6	3,790
3,0/3,0		5,050	
4,0/4,0		6,310	
4,5/3,6		3,530	
5,0/5,0		5,100	
168,3/139,7	7,1/6,3	8,430	
	3,0/2,6	3,660	
	3,0/3,0	4,880	
	4,0/4,0	6,100	
	4,5/4,0	3,420	
168,3/139,7	5,0/5,0	5,190	
	219,1/76,1	3,0/3,0	3,360
		219,1/88,9	2,0/2,0
4,0/4,0			5,240
219,1/88,9	5,0/5,0	6,560	
	219,1/114,3	3,0/2,6	6,110
3,0/3,0		8,150	
4,0/4,0		10,280	
5,0/5,0		5,760	
6,3/3,6		10,190	
219,1/139,7	3,0/2,6	6,180	
	3,0/3,0	8,250	
	4,0/4,0	10,310	
219,1/139,7	5,0/5,0	5,770	
	219,1/168,3	3,0/2,6	6,390
		3,0/3,0	8,530
4,0/4,0		10,660	
5,0/5,0		5,330	
219,1/168,3	6,3/4,5	11,520	
	273,0/88,9	3,0/3,0	8,580
4,0/4,0		11,450	
5,0/5,0		14,310	
273,0/114,3	3,0/3,0	8,850	
	5,0/5,0	14,750	
273,0/139,7	3,0/3,0	9,000	
	4,0/4,0	12,000	
	5,0/5,0	15,000	

# T-Stücke

## Reduzierte T-Stücke nahtlos/geschweißt



**Norm:** EN 10253-4 / DIN 2615 (nahtlos/geschweißt)  
**Abnahmen/Zeugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und Teilweise AD-W2  
 DIN 50049/3.1B Vormaterial  
**Werkstoff-Nr.:** 1.4301 / 1.4541 / 1.4571 / 1.4404 + Sonderwerkstoffe

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
273,0/168,3	2,0/2,0	6,100
	3,0/3,0	9,150
	4,0/4,0	12,200
273,0/219,1	3,0/3,0	9,520
	4,0/4,0	12,700
	5,0/5,0	15,870
323,9/114,3	3,0/3,0	12,500
	4,0/4,0	16,200
	5,0/5,0	20,830
323,9/139,7	3,0/3,0	12,260
	4,0/4,0	16,350
	5,0/5,0	20,430
323,9/168,3	3,0/3,0	11,130
	4,0/4,0	14,840
	5,0/5,0	18,550
323,9/219,1	3,0/3,0	11,430
	4,0/4,0	15,240
	5,0/5,0	19,050
323,9/273,0	2,0/2,0	7,980
	3,0/3,0	11,960
	4,0/4,0	15,950
	5,0/5,0	19,940

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
355,6/273,0	3,0/3,0	19,260
	4,0/4,0	25,680
	5,0/5,0	32,100
355,6/323,9	3,0/3,0	19,860
	4,0/4,0	26,480
	5,0/5,0	33,100
406,4/168,3	3,0/3,0	21,420
	4,0/4,0	28,560
	5,0/5,0	35,700
406,4/219,1	3,0/3,0	20,290
	4,0/4,0	27,050
	5,0/5,0	33,820
406,4/273,0	3,0/3,0	21,220
	4,0/4,0	28,290
	5,0/5,0	35,360
406,4/323,9	3,0/3,0	21,920
	4,0/4,0	29,230
	5,0/5,0	36,540
406,4/355,6	3,0/3,0	22,580
	4,0/4,0	30,100
	5,0/5,0	37,630

## T-Stücke nahtlos



**Norm:** EN 10253-4 / DIN 2615  
**Abnahmen/Zeugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2  
**Werkstoff-Nr.:** 1.4301 / 1.4541 / 1.4571 / 1.4404 + Sonderwerkstoffe

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
17,20	2,30	0,060
21,30	2,00	0,090
	2,60	0,100
	2,90	0,110
	3,60	0,130
	4,00	0,150
26,90	2,00	0,120
	2,30	0,150
	2,60	0,160
	2,90	0,180
	4,00	0,220

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
33,70	2,00	0,190
	2,60	0,250
	2,90	0,290
	3,60	0,350
	4,50	0,420
42,40	2,00	0,320
	2,60	0,410
	2,90	0,460
48,30	3,60	0,570
	2,00	0,460
	2,90	0,650

# T-Stücke

## T-Stücke nahtlos



**Norm:** EN 10253-4 / DIN 2615  
**Abnahmen/Zeugnisse:** DIN 50049/3.1B bzw. EN 10204/3.1B und AD-W2  
**Werkstoff-Nr.:** 1.4301 / 1.4541 / 1.4571 / 1.4404 + Sonderwerkstoffe

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
48,30	3,60	0,790
60,30	2,00	0,570
	2,90	0,830
	4,00	1,120
	5,60	1,500
76,10	2,90	1,250
	5,60	2,300
88,90	3,20	1,850
	5,60	3,100

Abmessungen		Gewicht KG/St.
ø- Aussen	Wandstärke	
114,30	3,60	3,100
	6,30	5,300
	8,80	7,500
139,70	4,00	4,800
168,30	4,50	7,250
	7,11	11,300
219,10	6,30	20,700
	8,18	27,700
	12,70	34,500

Andere Abmessungen oder Werkstoffe auf Anfrage.

Industriestraße 3 76470 Ötigheim Tel. 0 72 22 / 92 88 -12/18 Fax 0 72 22 / 92 88 -80  
e-mail: [info@edelstahlhandel-oetigheim.de](mailto:info@edelstahlhandel-oetigheim.de)